



BG-4K-88MA

8X8 4K UHD HDMI 2.0 MATRIX SWITCHER WITH AUDIO DE-EMBEDDING AND INDEPENDENT ROUTING (4K60 - 4:4:4 AND HDR SUPPORT)

With eight HDMI 2.0 inputs and eight HDMI 2.0 outputs, the BG-4K-88MA 4K HDMI matrix switch allows users to share up to eight HDMI sources with up to eight displays. Perfect for when you need to change multiple sources to show on various displays or even select just one source to show on all displays with the press of a button. Audio can also be independently routed. Professional-grade picture and audio quality are achieved with support for 4K resolutions and various high-quality audio formats.

The BG-4K-88MA supports high resolutions up to 4K@60Hz 4:4:4 with HDR. With 18 Gbps of uncompressed bandwidth, HDMI signals are routed with no loss of quality. All HDMI ports on this matrix are HDCP 2.2 compliant. This device is also equipped with autodownscaling on all outputs, ensuring compatibility with legacy displays. Additionally, the BG-4K-88MA supports Digital S/PDIF and Balanced audio output formats.



FEATURES



HDCP COMPLIANT

HDMI 2.0 (18Gbps) HDCP 2.2 (and all earlier versions supported)



4K RESOLUTION

Up to 4K@60Hz 4:4:4 HDR support



AUDIO MATRIXING

The audio can be independently routed



CONTROL OPTIONS

Control via front panel, IR, RS-232, and TCP/IP (Web GUI)



EDID MANAGEMENT

Seamless scaling for the best results



HDR SUPPORT

HDR, HDR10, Dolby Vision pass-through



TECH SPECIFICATIONS

_					•			ı
	0	\sim	h	n	П.	\sim	а	
- 11	_	•					a	

HDMI Compliance		HDMI 2.0b			
HDCP Compliance		HDCP 2.2			
Video Bandwidth		18Gbps			
Video Resolution		Up to 4K60Hz 4:4:4 640x480p60Hz, 800x600p60Hz, 10 1280x1024p60Hz, 1360x768p60Hz, 1440x1050p60Hz, 1600x1200p60Hz, 720x480i59.94Hz(480i59), 720x48 720x576i50Hz(576i50), 720x576p5 1280x720p50Hz(720p50), 1280x72: 1280x720p60Hz(720p60), 1920x10: 1920x1080i59.94Hz(1080i59), 1920x10: 1920x1080p23.98Hz(1080p23), 1920x1920x1080p25Hz(1080p25), 1920x1920x1080p30Hz(1080p30), 1920x1920x1080p30Hz(1080p30), 1920x1920x1080p59.94Hz(1080p59), 1923x340x2160p23.98Hz(2160p23), 38340x2160p25Hz(2160p25), 3840x3840x2160p30Hz(2160p30), 3840x3160p59.94Hz(2160p59), 3840x2160p59.94Hz(2160p59), 3840x2160p23.98Hz, 4096x2160p23, 4096x2160p29.97Hz, 4096x2160p2, 4096x2160p59.94Hz, 4096x2160p2, 4096x2160p2, 4096x2160p59.94Hz, 4096x2160p2,	, 1440x900p60Hz, z, 0p59.94Hz(480p59), 0Hz(576p50), 0p59.94Hz(720p59), 80i50Hz(1080i50), x1080i60Hz(1080i60), 20x1080p24Hz(1080p24), 1080p29.97Hz(1080p29), 1080p50Hz(1080p50), 20x1080p60Hz(1080p60), 40x2160p24Hz(2160p24), x2160p29.97Hz(2160p29), x2160p50Hz(2160p50), 40x2160p60Hz(2160p50), 40x2160p60Hz(2160p60), 24Hz, 4096x2160p50Hz, 80Hz, 4096x2160p50Hz,		
Color Space		RGB, YCbCr_4:4:4, YCbCr_4:2:2, YC	bCr_4:2:0		
Color Depth		8/10/12-bit			
HDR Formats		HDR, HDR10, HDR10+, Dolby Vision LLM, HLG			
Audio Formats		HDMI IN/OUT: LPCM, Dolby Digital/Plus/EX, Dolby EX, DTS-96/24, DTS High Res, DTS- AUDIO BREAKOUT: Optical outputs: Up to LPCM/Dolby/ Analog Audio Outputs: LPCM 2CH (s	-HD Master Audio, DSD DTS 5.1CH		
ESD Protection		IEC 61000-4-2: ±8kV (Air-gap dischdischarge)	narge) & ±4kV (Contact		
Recommended HDMI Cable	4K60	4K24	1080P		

The use of "Premium High Speed HDMI" cables is highly recommended.

5m/16ft

Limited Product Warranty Terms

Pro Line: 5-year warranty from the date of purchase for AV/Broadcasting products bought on or after August 1, 2024.

Essential Line: 3-year warranty from the date of purchase for AV/Broadcasting

products bought on or after August 1, 2024. **Cables:** Lifetime Limited Product Warranty.

For complete warranty information, please visit bzbgear.com/warranty. For questions, please call 1.888.499.9906 or email support@bzbgear.com.

Pro Line Products
5-YEAR WARRANTY
Essential Line Products
3-YEAR WARRANTY
Cables Products

LIFETIME WARRANTY

15m/49ft





HDMI Cable Length

(HDMI in / out)

10m/33ft



TECH SPECIFICATIONS

Connection

Input

8x INPUT [HDMI Type A, 19-pin female]

8x OUTPUT [HDMI Type A, 19-pin female]

8x OPTICAL AUDIO OUT

8x L/R AUDIO OUT [5-pin phoenix connector]

1x TCP/IP [RJ45]

 Control
 1x RS-232 [D-Sub9]

 1x IR EXT [3.5mm audio jack]

Mechanical

Housing Metal Enclosure Color Black Dimensions (WxDxH) 17in x 8.1in x 1.8in [440mm x 206mm x 44.5mm] Weight 5.25 lbs [2.38kg] Input: AC 100 - 240V 50/60Hz, **Power Supply** Output: DC 24V/3.75A (US/EU standard, CE/FCC/UL certified) Full Load: 52.3W; **Power Consumption** Stand-by: 2.6W **Operating Temperature** 32 - 104°F / 0 - 40°C -4° - 140°F / -20° - 60°C Storage Temperature **Operating Humidity** 20%~80% relative humidity, non-condensing Storage Humidity 10%~90% relative humidity, non-condensing



Limited Product Warranty Terms

Pro Line: 5-year warranty from the date of purchase for AV/Broadcasting products bought on or after August 1, 2024.

Essential Line: 3-year warranty from the date of purchase for AV/Broadcasting products bought on or after August 1, 2024.

Cables: Lifetime Limited Product Warranty.

For complete warranty information, please visit bzbgear.com/warranty.
For questions, please call 1.888.499.9906 or email support@bzbgear.com.

Pro Line Products
5-YEAR WARRANTY
Essential Line Products
3-YEAR WARRANTY
Cables Products
LIFETIME WARRANTY

