



# **BG-STREAM-E**

HDMI TO IP/UVC POE ENCODER SUPPORTS H.264/ H.265/AVC (DANTE AV-H READY)

The BG-STREAM-E HDMI to IP/UVC is a compact and efficient video converter that provides a seamless connection between HDMI inputs and IP or USB 3.0 UVC outputs. This device is ideal for high-definition video streaming and recording, offering robust features such as hardware compression, real-time recording, and support for multiple streaming protocols.

Supporting resolutions up to 1920x1080p at 60/50fps, the BG-STREAM-E delivers exceptional video quality. The device features advanced video processing with H.265/H.264/AVC encoding, enabling efficient compression without compromising performance. Audio support includes AAC-LC with a configurable bit rate range from 32Kbps to 384Kbps and a sample rate of 48KHz, ensuring clear and synchronized audio.



### **FEATURES**



#### VERSATILE CONNECTION OPTIONS

HDMI, USB 3.0, and IP connections, including support for Dante AV-H and NDI|HX



#### HIGH-QUALITY VIDEO PROCESSING

Capable of resolutions up to 1920x1080p at 60/50fps

# **d**hlh

#### AUDIO SUPPORT

Features AAC-LC audio codec with configurable bit rate range



#### NETWORK CAPABILITIES

Includes DHCP support and Power over Ethernet (POE) functionality



#### USER-FRIENDLY INTERFACE

Accessible web UI for easy system configuration



#### EXTENSIVE PROTOCOL SUPPORT

Compatible with RTSP, RTMP, HLS, TS, SRT, NDI HX, and Dante AV-H



## **TECH SPECIFICATIONS**

#### **Technical**

| Input Interface            | Video:<br>1x HDMI  |
|----------------------------|--|
| Output Interface           | Video:<br>1x RJ45 (RTSP/RTMP/HLS/TS/SRT/NDI HX/Dante AV-H Support)<br>1x USB 3.0 Type B (UVC) output   |
| Video Support              | H.265/H.264/AVC, Baseline/Main/High Profile<br>Supported HDMI output Resolutions:<br>1920x1080p@60/50fps<br>1920x1080i@60/50fps<br>1920x1080i@60/50fps<br>1280x720p@60/50fps<br>1280x1024p@60fps<br>1280x960p@60fps<br>1024x768p@60fps<br>800x600p@60fps<br>640x480p@60fps<br>720x480p@60fps<br>720x576p@50fps |
| Audio Support              | AAC-LC<br>Configurable bit rate range from 32Kbps to 384Kbps<br>Sample rate: 48KHz, 16bit  |
| Max. FPS                   | 1920x1080p@60/50fps  |
| Network / Ethernet Support | 1x RJ45 for 10/100/1000Mbps Ethernet<br>DHCP Client  |
| Streaming Protocol Support | NDI Support (Separate License with NDI Required)<br>Dante AV-H (Separate License with Dante AV-H Required)<br>RTSP over UDP/TCP/Multicast/HTTP<br>RTMP (Publish)<br>TS over IP<br>HLS  |
| Additional Features        | UVC Device Supported<br>Web UI for System Configuration<br>Firmware Upgradable   |
| Power Supply               | DC Input<br>PoE Support  |
| Unit Dimensions            | 4.1in x 2.8in x 1in [103.8mm x 71.2mm x 26mm]  |
|                            |  |

#### **Limited Product Warranty Terms**

**Pro Line:** 5-year warranty from the date of purchase for AV/Broadcasting products bought on or after August 1, 2024.

Essential Line: 3-year warranty from the date of purchase for AV/Broadcasting products bought on or after August 1, 2024.Cables: Lifetime Limited Product Warranty.

For complete warranty information, please visit **bzbgear.com/warranty**. For questions, please call **1.888.499.9906** or email **support@bzbgear.com**.



830 National Drive, Suite 140 Sacramento, CA 95834

Pro Line Products

**5-YEAR WARRANTY** 

**3-YEAR WARRANTY** 

LIFETIME WARRANTY

1.888.499.9906 info@bzbgear.com