



BG-8K-DA12A-G2

1X2 8K UHD HDMI 2.1 48GBPS SPLITTER WITH AUTO DOWNSCALING/AUDIO DE-EMBEDDER (8K60/4K120 AND VRR/FVA/ALLM SUPPORT)

The BG-8K-DA12A-G2 is a high-performance 1x2 HDMI 2.1 splitter designed to distribute a single HDMI source to two displays without compromising video or audio quality. Supporting resolutions up to 8K@60Hz (4:2:0, 12-bit) and 4K@120Hz (4:4:4, 12-bit) with 48Gbps FRL bandwidth, this device ensures stunning visual clarity and fluid motion for both home entertainment and professional AV setups. Its HDCP 2.3 compliance guarantees seamless content protection, making it ideal for high-definition streaming, gaming, and presentation applications.

Engineered for superior performance, the BG-8K-DA12A-G2 integrates cutting-edge technologies, including HDR, HDR10+, Dolby Vision, and HLG pass-through, to deliver deeper contrast, vibrant colors, and enhanced image quality. Gamers will benefit from VRR (Variable Refresh Rate), FVA (Fast VActive), and ALLM (Auto Low Latency Mode), ensuring smooth gameplay and reduced input lag. Additionally, built-in audio de-embedding extracts high-fidelity audio via optical (S/PDIF) and 3.5mm analog outputs, offering versatile sound output options for home theaters and professional AV setups.



FEATURES



8K HDMI 2.1 SUPPORT

Supports up to 8K@60Hz (4:2:0, 12-bit) and 4K@120Hz (4:4:4, 12-bit) for ultrasmooth visuals and deep color



HDCP 2.3 COMPLIANCE

Secures content protection for streaming devices, gaming consoles, and Blu-ray players



HDR & ADVANCED VIDEO

Supports HDR, HDR10+, Dolby Vision, and HLG for enhanced brightness, contrast, and color depth



CONTENT-OPTIMIZED

Features VRR, FVA, and ALLM for reduced lag and screen tearing



AUDIO DE-EMBEDDING

Extracts audio via optical (S/PDIF) and 3.5mm analog outputs for external sound systems



ADVANCED EDID MANAGEMENT

Customizable EDID settings ensure seamless source-display communication



TECH SPECIFICATIONS

TOO	hnical
	11111634

Connection	Mechanical		
ESD Protection	IEC 61000-4-2: ±8kV (Air-gap discharge) & ±4kV (Contact discharge)		
HDR	HDR, HDR10, HDR10+, Dolby Vision, HLG		
Audio Formats	HDMI Input/Output: LPCM, Dolby Digital/Plus/EX, Dolby True HD, Dolby Atmos, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DSD Technical Audio De-embedded Output: Optical: LPCM/Dolby/DTS 5.1CH Analog: LPCM 2CH		
Color Space	RGB, YCbCr_4:4:4, YCbCr_4:2:2, YCbCr_4:2:0		
Color Depth	8/10/12bit		
Video Resolution	Up to 8K@60Hz 4:2:0 12bit, 4K@120Hz 4:4:4 12bit		
Video Bandwidth	48Gbps FRL and 18Gbps TMDS		
HDCP Compliance	HDCP 2.3, HDCP 1.4		
HDMI Compliance	HDMI 2.1		

Connection

Connection		Mechanical	
Input 1 x HDMI IN [Type A, 19-pi	1 x HDMI IN [Type A, 19-pin female]	Housing	Metal Enclosure
		Dimensions (W x D x H)	5.7in x 2.7in x 0.67in [145mm x 68mm x 17mm]
		Weight	0.57 lbs [260g]
Output	2 x HDMI OUT [Type A, 19-pin female] 1 x OPTICAL [S/PDIF] 1 x L/R [3.5mm Stereo Mini-jack]	Power Supply	Input: AC 100-240V 50/60Hz, Output: DC 5V/2A (US/EU standards, CE/FCC/UL certified)
Control	1 x SERVICE [USB Type C, Update port]	Power Consumption	4.5W (Max)
		Operation Temperature	32°F ~ 104°F / 0°C ~ 40°C
		Storage Temperature	-4°F ~ 140°F / -20°C ~ 60°C
		Relative Humidity	20~90% RH (non-condensing)

Recommended HDMI Cable	8K	4K60	4K24	1080P
HDMI Cable Length (HDMI in / out)	3m/10ft (Ultra HDMI 2.1)	8m/26ft	12m/39ft	15m/49ft

The use of "Premium High Speed HDMI" cables is highly recommended.

Limited Product Warranty Terms

Pro Line: 5-year warranty from the date of purchase for AV/Broadcasting products bought on or after August 1, 2024.

Essential Line: 3-year warranty from the date of purchase for AV/Broadcasting products bought on or after August 1, 2024.

Cables: Lifetime Limited Product Warranty.

For complete warranty information, please visit bzbgear.com/warranty. For questions, please call 1.888.499.9906 or email support@bzbgear.com.

Pro Line Products **5-YEAR WARRANTY 3-YEAR WARRANTY**

LIFETIME WARRANTY



